


OPF**L**F1D1*



Model	Displacement (ml/r)	Pressure(bar)		Speed(r/min)			L(mm)	L1(mm)
		Rated	Peak	Rated	Max.	Min.		
OPF0.16L61F1D1*	0.16	200	250	3000	6000	800	57.7	26.9
OPF0.25L61F1D1*	0.25	200	250	3000	6000	800	58.5	27.3
OPF0.38L61F1D1*	0.38	200	250	3000	6000	800	59.8	27.9
OPF0.50L61F1D1*	0.50	200	250	3000	6000	800	60.5	28.3
OPF0.63L61F1D1*	0.63	200	250	3000	6000	800	62.0	29.0
OPF0.75L61F1D1*	0.75	200	250	3000	6000	800	63.0	29.5
OPF1.00L61F1D1*	1.00	200	250	3000	6000	800	65.5	30.8
OPF1.25L61F1D1*	1.25	200	250	3000	5000	800	68.0	32.0
OPF1.50L61F1D1*	1.50	200	250	3000	5000	800	70.0	33.0
OPF1.75L61F1D1*	1.75	160	200	3000	4500	800	72.5	34.3
OPF2.00L61F1D1*	2.00	160	200	3000	4500	800	75.0	35.5

Dimensions

